

WEFTMASTER® SFB-L

MODEL RECOMMENDATION

Requirements	Spring Brake			Combi- nation	Deviation Brake		
	Chromium spring brake long 40635000	Ceramic spring brake short 42793000	Double Ceramic spring brake short 43097000	Spring and Deviation Brake 43789000	Deviation Brake 2-fold 39820010, 4-fold 37595030, 5-fold 41378000	Double Deviation Brake 2-fold 40849000, 4-fold 40237000	Triple Deviation Brake 2-fold 43680000
Blended yarns coarser than Nm 10							
Bolting cloth							
Bouclé- and Fancy yarn							
Cotton							
Filament textured							
Glass coated							
Glass plain							
Glass textured							
Hair yarn twisted multifilament							
Jute							
Linen							
Lurex							
Monofilament							
Monofilament stiff from 3000 den							
Multifilament zero twist							
Polyethylene from 3000 den							
Polyethylene to 3000 den							
Polypropylene from 3000 den							
Polypropylene to 3000 den							
Rafia							
Ribbon all materials from 3000 den							
Ribbon all materials to 3000 den							
Spun rayon							
Weak yarns							
Weft threads with low tensile strength							
Weft threads with medium tensile strength							
Woollen yarn from Nm 28 and finer							
Worsted yarn simple							
Yarn count less Nm 30 / tex 34							

Legend: recommended further recommended